



# LINA ETANJ V.3

Surface Mounted 31 W Etanj LED Luminaire

Order Code : 3107312  
 Product Code : LNE 030U 40OD00 3K9 125 PG V.3



## Product Data

### Standard Features

Housing	: Aluminium extrusion housing, pg cable gland
Diffuser	: Glare controlled opal diffuser
IP Grade	: IP65
Installation	: Surface mounted
Light Source	: Mid Power LED


### Optical & Electrical Features

Power Consumption	: 30.9 W
Final Luminous Flux	: 3954 lm
Efficacy	: 127.8 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: > 0,9
Surge Transient Protection	: 1 kV
Drive Current	: 700 mA
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

### Other Features & Conditions

Operating Temperature Range	: -20 °C/+40 °C
Operating Temperature Range With Emergency Kit	: +5 °C/+35 °C
Impact Resistance	: IK09
Led Life Time - L70	: > 72.000 saat @Ta= 40 °C

## Photometric Curve




### Optional Features

Correlated Color Temperatures	: 3000K, 5700K, 6500K
Emergency Kit Options	: 1, 3 hours
DALI Option	: Yes
Sensor	: Yes

# LINA ETANJ V.3

Surface Mounted 31 W Etanj LED Luminaire

3107312 LNE 030U 40OD00 3K9 125 PG V.3




Dimension (mm)


	a	b	h	d
Standard	1265	65	83	15
With Emergency Kit (1 hr.)	1265	65	83	15
With Emergency Kit (3 hrs.)	1265	65	83	15
With Sensor	1372	65	83	15

Weight (kg)


Standard	2,2
With Emergency Kit (1 hr.)	2,7
With Emergency Kit (3 hrs.)	3,1
With Sensor	2,5



## Suspension Set



Stainless steel suspension set



Top View

- EAE, reserves the right to make changes without prior notice.



Revision date: 28.06.2019