REVOLED-S SC
V.3

Surface Mounted 38 W LED High Bay Luminaire

Order Code	: 3158944
Product Code	: RVL 038U 40TF00 90 5K58 V3 PC

Product Data

Standard Features

Housing	: Aluminium profile housing, poli carbon side cover
Diffuser	: Tempered glass with security film
Optic	: High reflectance PC reflector
IP Grade	: IP65
Installation	: Surface Mounted
Light Source	: Mid Power LED

Optical & Electrical Features

Power Consumption	: 38.1 W
Final Luminous Flux	: 5483 lm
Efficacy	: 143.6 lm/w
Input Voltage	: 220-240 V
Frequency	: 50-60 Hz
Power Factor	: > 0,9
Surge Transient Protection	: 1 kV
Drive Current	: 300 mA
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

Photometric Curve



Other Features & Conditions

Operating Temperature Range	: -20 °C/+45 °C
Operating Temperature Range With Emergency Kit	: +5 °C/+30 °C
Impact Resistance	: IK10
Led Life Time - L70	: > 72.000 hours @Ta= 40 °C

Optional Features

Correlated Color Temperatures	: 3000K, 5700K, 6500K
Emergency Kit Options	: 1, 3 hours
DALI Option	: Yes

REVOLED-S SC V.3

Surface Mounted 38 W LED High Bay Luminaire

3158944 RVL 038U 40TF00 90 5K58 V3 PC





Dimension (mm)

	a	b	h
Standard	585	220	74
With Emergency Kit (1, 3 hrs.)	585	220	74
DALI	585	220	74

Weight (gr)

Standard	4
With Emergency Kit (1, 3 hrs.)	4.7, 4.9

Suspension Set



Revoled Poli Carbon Busbar Hanger Set
Product Code : 3163889

a	b	c	Weight (gr)
50mm	48mm	162mm	312



Revoled Poli Carbon Cable Tray and Wall Hanger Set
Product Code : 3163476

a	b	c	Weight (gr)
50mm	48mm	70mm	191



Wall-Mounted Hanger Set
With 10° Angular Adjustment Steps
Product Code : 3080656

a	b	c	Weight (gr)
110mm	89mm	290mm	-

- EAE, reserves the right to make changes without prior notice.

engineering the light

EAE Aydınlatma A.Ş.
İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TURKEY **Phone:** +90 212 413 21 00 (pbx) **Fax:** +90 212 549 37 90
www.eaeaydinlatma.com.tr

Revision date: 02.04.2019